

吊衣桿燈系列 RN006



產品特色 Product Features

- ☆ 無紫外線 Non ultraviolet (UV) rays
- ☆ 省電環保 Energy saving and environment protection
- ☆ 鋁製外殼 Aluminum case
- ☆ 50,000 小時壽命 Life times : $\geq$ 50,000 hours (HRS)

適用場所 Applications

- ☆ 住宅 House lighting
- ☆ 藝廊 Gallery lighting
- ☆ 展示櫃 Display cupboards
- ☆ 商業空間 Commercial area

型號	Model	POWER(W)	VIEW ANGEL	COLOR TEMP	LUX@80	CRI	長度(mm)
RN006-45-C	正白	5W	120°	5700K	180lux	80	413
RN006-45-N	暖黃	5W	120°	4000K	160lux	80	413
RN006-45-W	黃光	5W	120°	3000K	140lux	80	413
RN006-60-C	正白	7W	120°	5700K	190lux	80	563
RN006-60-N	暖黃	7W	120°	4000K	170lux	80	563
RN006-60-W	黃光	7W	120°	3000K	150lux	80	563
RN006-80-C	正白	9W	120°	5700K	200lux	80	763
RN006-80-N	暖黃	9W	120°	4000K	180lux	80	763
RN006-80-W	暖白	9W	120°	3000K	160lux	80	763
RN006-90-C	正白	10W	120°	5700K	210lux	80	863
RN006-90-N	暖黃	10W	120°	4000K	190lux	80	863
RN006-90-W	黃光	10W	120°	3000K	170lux	80	863
RN006-100-C	正白	11W	120°	5700K	220lux	80	963
RN006-100-N	暖黃	11W	120°	4000K	200lux	80	963
RN006-100-W	黃光	11W	120°	3000K	190lux	80	963
RN006-120-C	正白	13W	120°	5700K	240lux	80	1163
RN006-120-N	暖黃	13W	120°	4000K	220lux	80	1163
RN006-120-W	黃光	13W	120°	3000K	200lux	80	1163

Item / 項目	Description / 說明
Housing Material / 機構材料	鋁
Input Voltage / 輸入電壓範圍	AC110~220V 3000K / 4000K / 5700K
Light Power Consumption / 光源耗電	5W/7W /9W/10W/11W/13W
Operating Temperature / 工作環境溫度	70°CMax.
Color Temperature / 色溫	3000K / 4000K / 5700K
LED CRI / 光源演色性	80~85 Typical
Illuminance / 照度	180 lux@80cm typ.
Radiation Angle / 輻射(發光)角度	120 度
Life Time / 壽命	50,000 hrs